



CHARGED WITH POSSIBILITIES

Battery technology has come of age, and we leave no stone unturned in the pursuit of excellence for our battery-powered construction equipment. By bringing together all the insight and innovation at Husqvarna, we keep our customers right at the forefront of new developments. With proven battery performance and reliability in more demanding applications, our machines provide major benefits for you, your business and society.

Go to husqvarnaconstruction.com for more information.

HUSQVARNA PACE™ BATTERY SYSTEM

So much more becomes possible with the high power delivered by the PACE™ system of 94V battery-powered products. The battery is available in two sizes and delivers high performance for demanding professionals on the go. Machines using this growing system are setting high standards for the industry. Husqvarna K1 PACE has been recognised with a Red Dot design award for user-friendly design, a PITA Tool Innovation Award and a nomination for a World Demolition Award for innovation.



POWER CUTTER
HUSQVARNA K1 PACE
7.2/7.4 kg, blade size 300/350 mm, cutting depth 121/144.5 mm.



POWER CUTTER
HUSQVARNA K1 PACE RESCUE
7.9 kg, blade size 350 mm, cutting depth 144.5 mm.

NEW



POWER CUTTER
HUSQVARNA K1 PACE RAIL
7.9 kg, blade size 356 mm, cutting depth 133 mm, PACE 94V battery system.

NEW



DRILL MOTOR
HUSQVARNA DM 1 PACE
2.5 kW, recommended drill diameter 25–400 mm, 17.3 kg (incl. battery).

NEW



DUST EXTRACTOR
HUSQVARNA DE 120 H PACE
High safety standards. Easy to transport. Operate more sustainably with e-flow, 480 m³/h, 41 kg.

ACCESSORIES PACE™



BATTERIES
HUSQVARNA B380X/B750X PACE
High-power 94V PACE™ batteries equipped with built-in connectivity. Capacity: 375/750 Wh, weight 3/5 kg.



CHARGERS
HUSQVARNA C900X/C1800X
High-power battery chargers with a fast charging mode and active cooling. Power 900 W/1800 W.



BATTERY BOX
HUSQVARNA PACE BATTERY BOX
A sturdy, durable wooden box for the convenient protection and transportation of two PACE batteries and one charger. UN 3480 certified for transporting lithium-ion batteries.



K1 PACE VAC ATTACHMENT
Ideal dust collection enables you to cut without water.

DIAMOND BLADES PACE™



B **HUSQVARNA TACTI-CUT S 35 S PACE**
Providing a good balance between performance and price in all cutting operations. Low vibrations with the continuous rim and silence core.



S **HUSQVARNA ABRASIVE DISCS**
Conventional abrasive disc especially recommended for cutting metal and rebars. Suitable for use in standard PC.



S **HUSQVARNA VARI-CUT FR3**
Has one layer of vacuum-brazed diamonds for the fast cutting of a large variety of materials like tile, stone, rebars, fiber board, PVC pipe and more. Suitable for use in standard PC.

HUSQVARNA BLi BATTERY SYSTEM

Power meets versatility with our BLi system of 36V battery-powered products. Lightweight and powerful, the system is versatile for a variety of construction applications and is compatible with a wide range of Husqvarna tools for forestry and landscaping. The tools have been optimised to provide higher performance and better utilisation of battery power.

NEW



POWER CUTTER
HUSQVARNA K 540i
4.17 kg, blade size 267 mm, cutting depth 100 mm.



POWER CUTTER
HUSQVARNA K 535i
3.5 kg, blade size 230 mm, cutting depth 76 mm.

NEW



FORWARD PLATE COMPACTOR
LF 60i LAT
1.2 kW, 350 mm, 69 kg. Ideal for hardscaping work. Includes water tank, transport wheels and low-vibration handle. Optional block paving kit available.



DUST EXTRACTOR
HUSQVARNA DE 110i H
Versatile and compact H-class dust extractor. 215 m³/h, 26 kg.



DRILL MOTOR
HUSQVARNA DM 540i
1350 W, recommended drill diameter 15–75 mm (100 mm with drill stand), 4.9 kg.



BATTERY SREED
HUSQVARNA BV 30i
Output power 0.8 kW, weight 11.5 kg.

ACCESSORIES BLi



CHARGERS
HUSQVARNA QC330/QC500
Quick-charging unit with 2-LED status indicator and active battery cooling for minimum charging time and longer battery life.



BATTERIES
HUSQVARNA BLi 200/300
Sturdy construction and excellent cooling. Rechargeable more than 1,500 times. 5/8.9 Ah, 1.3/1.9 kg.



K 540i AND K 535i VAC ATTACHMENTS
Ideal dust collection enables you to cut without water.



WATER TANK
HUSQVARNA WT 15i
Compact and easy-to-use water tank with electric pump. Has a capacity of 15 litres and allows for continual cutting for 45 minutes. Battery-powered, 36 V BLi system.



WORKING LIGHT
HUSQVARNA WL 8i
Extremely durable and powerful – up to 8000 lumen. Easy to carry and position, change from flood light to 360 degree area light using the light diffuser accessory. Built-in power bank with USB outlet. Tripod accessory gives an adjustable height between 1.35 and 3 m. Max run time 48 hours (with BLi 300), 3.5 kg.



HUSQVARNA BATTERY BOX PLYWOOD
A sturdy, durable wooden box for the convenient protection and transportation of two BLi batteries and one charger. UN 3480 certified for transporting lithium-ion batteries.

DIAMOND TOOLS BLi



G HUSQVARNA ELITE-CUT S 35 S BAT
Developed for smooth and fast cutting in diverse materials such as concrete, brick, blocks and natural stone. With this blade you will experience reduced side friction, lower vibrations, and better slurry evacuation.



B HUSQVARNA TACTI-CUT S 35 S BAT
Optimised for cutting in materials such as concrete, brick, blocks and natural stone. Thanks to the segment shape and composition, the blades provide an easier and freer cut, which results in reduced vibration levels and a smoother cutting experience.



S HUSQVARNA VARI-DISC STEEL
Conventional abrasive disc especially recommended for cutting metal and rebars.



S HUSQVARNA VARI-CUT FR3
Has one layer of vacuum-brazed diamonds for the fast cutting of a large variety of materials like tile, stone, rebars, fibre board, PVC pipe and more.



NEW



NEW



G HUSQVARNA ELITE-DRILL D 10 TW
For handheld drilling in brick and lightly reinforced concrete. Wet drilling.

G HUSQVARNA ELITE-DRILL D 1610
Developed and optimised for DM 1 PACE. For lower power ratings of 2.5–3 kW.

G HUSQVARNA ELITE-DRILL D65 DRY
Main drill bit for DM 540i. Allows drilling in sensitive environments or when water is not accessible.

OTHER BATTERY PRODUCTS

The range of battery-powered products from Husqvarna is constantly expanding to maximise the benefits and take more of the strain out of your daily work.



FORWARD PLATE COMPACTOR
HUSQVARNA LFe 60 LAT
1.8 kW, 350 mm, 88 kg. Runs on Honda eGX battery platform, specifically developed for compaction applications.

NEW



HANDHELD GRINDER
HUSQVARNA HG 125 B
1500 W equivalent, grinding width 125 mm, disc speed 11000 rpm, 2.2 kg (excl. battery). Compatible with all new and existing Bosch Professional 18 V tools and chargers.

WE'LL LET NOTHING STOP YOU FROM SAWING AND DRILLING

Our range of wall and wire saws, floor saws, handheld power cutters, core drills and diamond tools are among the widest and most powerful in the world. This means that whatever job you're up to, we can provide the equipment you need to meet your challenge. Go to husqvarnaconstruction.com for more information.

DIAMOND BLADES WITH SMARTER FEATURES

To help customers use products safely, and experience better performance when operating a handheld power cutter, Husqvarna offers smarter features in the Elite-Cut, Vari-Cut and Tacti-Cut series. The smarter features give the operator a clear and immediate overview of the blade's wear, side clearance, direction of rotation and intended application.

DIAMOND TOOLS IN THREE PERFORMANCE LEVELS

Husqvarna diamond tools come in three performance levels: ELITE, VARI and TACTI, represented by the colours Gold, Silver and Bronze, respectively.

ELITE

Our ELITE diamond tools are developed for highly demanding professionals working on specialist applications and intensive jobs. They provide maximum cutting speed and wear resistance in heavy cutting, grinding and drilling.

VARI

Our VARI diamond tools are developed for demanding professionals doing a variety of quick jobs during a workday in various all-round applications. They provide high cutting speed and wear resistance in all cutting, grinding and drilling.

TACTI

Our TACTI diamond tools are developed for demanding professionals working occasionally with cutting and drilling jobs, looking for the best value between performance and price in all common cutting and drilling applications.



CONCRETE CORE DRILLS, DRILL MOTORS WITH STANDS AND DRILL STANDS



BATTERY-POWERED

HUSQVARNA DM 540i

1350W, recommended drill diameter 15–75 mm (100 mm with drill stand), 4.9 kg. BLi 36V battery system.

NEW



BATTERY-POWERED

HUSQVARNA DM 1 PACE

2.5 kW, recommended drill diameter 25–400 mm, 17.3 kg (incl. battery).



ELECTRIC-POWERED

HUSQVARNA DM 700

6000/3000W, 3-phase/1-phase, recommended drill diameter 80–600 mm, 14 kg.



ELECTRIC-POWERED

HUSQVARNA DM 430

3200W, 1-phase, recommended drill diameter 100–450 mm, 15.5 kg.



ELECTRIC-POWERED

HUSQVARNA DM 400

3200W, 1-phase, recommended drill diameter 55–350 mm, 14 kg.



ELECTRIC-POWERED

HUSQVARNA DM 370

3200W, 1-phase, recommended drill diameter 25–250 mm, 14 kg.



HYDRAULIC-POWERED

HUSQVARNA DM 406 H

120/230/340/580/980/1400 rpm, recommended drill diameter 0–650 mm, 16 kg.



ELECTRIC-POWERED

HUSQVARNA DM 230

1850W, 1-phase, recommended drill diameter 150 mm, handheld 80 mm, 7 kg.



ELECTRIC-POWERED

HUSQVARNA DM 220

1850W, 1-phase, recommended drill diameter 150 mm, handheld 80 mm, 7.5 kg.



ELECTRIC-POWERED

HUSQVARNA DM 200


2000W, 1-phase, recommended drill diameter 25–100 mm, 6.4 kg.



ELECTRIC-POWERED

HUSQVARNA DMS 240

2400W, 1 phase, max Ø 250 mm, 20.4 kg.



ELECTRIC-POWERED

HUSQVARNA DMS 160 AT

1550W, 1 phase, max Ø 120 mm, 10.5 kg.



ELECTRIC-POWERED

HUSQVARNA DMS 160 A

1550W, 1 phase, max Ø 120 mm, 12 kg.



HUSQVARNA DS 900

Ø 900 mm, travel length 950 mm, 24 kg.



HUSQVARNA DS 500

Ø 500 mm, travel length 706 mm, 18 kg.



HUSQVARNA DS 250/DS 250 SINGLE SPEED

Ø 250 mm, travel length 685 mm, 16 kg.



HUSQVARNA DS 150

Ø 150 mm, travel length 495 mm, 15.5 kg.



HUSQVARNA DS 50 COMBI

Ø 300 mm, travel length 1090 mm, 21 kg.



HUSQVARNA DS 50 GYRO

Ø 350 mm, travel length 670 mm, 56 kg.



HUSQVARNA DS 40 GYRO

Ø 150 mm, travel length 600 mm, 30 kg.

DIAMOND CORE DRILL BITS

G
S

HUSQVARNA ELITE-DRILL TW AND VARI-DRILL TW SERIES

ELITE-DRILL TW series is specially designed for battery-powered and low-powered handheld drill motors. Experience faster and smoother drilling with a quick and precise start. ELITE-DRILL TW is a range of thin walled drill bits for wet drilling. 1/2" gas connector.



G

HUSQVARNA ELITE-DRILL D1600 SERIES

ELITE-level drill bits that deliver smooth, fast drilling in demanding applications. Available for various materials like heavily reinforced concrete, hard aggregate and abrasives. Diameters 92–350 mm.



S

HUSQVARNA VARI-DRILL

VARI-level drill bits with great performance and durability in heavy-duty applications. Diameters from 18–300 mm in two versions depending on the application. 1 1/4" connector.



B

HUSQVARNA TACTI-DRILL

TACTI-level drill bits with a good price/performance value for non-intensive use in heavier applications. Diameters from 52–300 mm. 1 1/4" connector.



S

HUSQVARNA VARI-DRILL DRY

Lightweight drill bits for dry indoor drilling by specialist professionals. Two versions available. Vacuum-brazed segments for drilling tile and natural stone. Diameters 5–85 mm. Laser-welded segments for drilling concrete, brick, and cement blocks. Diameters 37–200 mm.



POWER CUTTERS



BATTERY-POWERED

HUSQVARNA K1 PACE

7.2/7.4 kg, blade size 300/350 mm, cutting depth 121/145 mm, PACE 94V battery system.



BATTERY-POWERED

HUSQVARNA K1 PACE RESCUE

7.9 kg, blade size 350 mm, cutting depth 145 mm, PACE 94V battery system.

NEW



BATTERY-POWERED

HUSQVARNA K1 PACE RAIL

7.9 kg, blade size 356 mm, cutting depth 133 mm, PACE 94V battery system.



BATTERY-POWERED

HUSQVARNA K535i

3.5 kg, blade size 230 mm, cutting depth 76 mm. BLi 36V battery system.

NEW



POWER CUTTER

HUSQVARNA K540i

4.17 kg, blade size 267 mm, cutting depth 100 mm.



PETROL-POWERED

HUSQVARNA K1270

119 cc, 5.8 kW, 13.3/13.7 kg, blade size 350/400 mm, cutting depth 118/145 mm.



PETROL-POWERED

HUSQVARNA K1270 SMARTGUARD

119 cc, 5.8 kW, 15.1 kg, blade size 400 mm, cutting depth 118/145 mm.



PETROL-POWERED

HUSQVARNA K970

94 cc, 4.8 kW, 11/11.6 kg, blade size 350/400 mm, cutting depth 125/155 mm.



PETROL-POWERED

HUSQVARNA K970 SMARTGUARD

94 cc, 4.8 kW, 11.9/12.8 kg, blade size 350/400 mm, cutting depth 125/155 mm.



PETROL-POWERED

HUSQVARNA K770 / K770 WITH OILGUARD

74 cc, 3.7 kW, 10/10.1 kg, blade size 300/350 mm, cutting depth 100/125 mm.



PETROL-POWERED

HUSQVARNA K770 SMARTGUARD

74 cc, 3.7 kW, 10.8/11.1 kg, blade size 300/350 mm, cutting depth 100/125 mm.



PETROL-POWERED

HUSQVARNA K770 VAC

74 cc, 3.7 kW, 11.0 kg, blade size 305 mm, cutting depth 123 mm.



PETROL-POWERED

HUSQVARNA K770 DRY CUT

74 cc, 3.7 kW, 12.0 kg, blade size 305 mm, cutting depth 123 mm.



PETROL-POWERED

HUSQVARNA K970 RING

94 cc, 4.8 kW, 13.8/14.2 kg, blade size 370/430 mm, cutting depth 270/325 mm.



PETROL-POWERED

HUSQVARNA K760 CUT-N-BREAK

74 cc, 3.7 kW, 11.1 kg, blade size 230 mm, cutting depth 400 mm.



PETROL-POWERED

HUSQVARNA K970 CHAIN

94 cc, 4.8 kW, 9.7 kg, bar size 350 mm, cutting depth 400 mm.



PETROL-POWERED

HUSQVARNA K1270 RAIL

119 cc, 5.8 kW, 20.5/21.2 kg (incl. RA10), blade size 350/400 mm, cutting depth 118/145 mm.



PETROL-POWERED

HUSQVARNA K970 RESCUE

94 cc, 4.8 kW, 11 kg, blade size 350 mm, cutting depth 125 mm.



PETROL-POWERED

HUSQVARNA K770 RESCUE

74 cc, 3.7 kW, 9.6 kg, blade size 300 mm, cutting depth 100 mm.



HYDRAULIC-POWERED

HUSQVARNA K3600 MK II

150 bar/401 min, 4.3 kW, 8.3 kg, blade size 370 mm, cutting depth 270 mm.



HYDRAULIC-POWERED

HUSQVARNA K2500

150 bar/401 min, 5.2 kW, 8.3 kg, blade size 400 mm, cutting depth 145 mm.



AIR-POWERED

HUSQVARNA K400

7 kp/cm², 3.2 kW, 9.9 kg, blade size 350 mm, cutting depth 125 mm.



ELECTRIC-POWERED

HUSQVARNA K7000

230/400 V, 5.5 kW (3-phase)/3 kW (1-phase), 9.8 kg, blade size 400 mm, cutting depth 155 mm.



ELECTRIC-POWERED

HUSQVARNA K7000 SMARTGUARD

230/400 V, 5.8 kW (3-phase)/3 kW (1-phase), 5.1 kg, blade size 400 mm, cutting depth 145 mm.



PETROL-POWERED

HUSQVARNA K7000 RING

230/400 V, 5.5 kW (3-phase)/3 kW (1-phase), 13.1/12.4 kg, blade size 350/425 mm, cutting depth 270/325 mm.



ELECTRIC-POWERED

HUSQVARNA K4000 CHAIN

230/400 V, 5.5 kW (3-phase)/3 kW (1-phase), 9.1 kg, bar size 450 mm, cutting depth 450 mm.



ELECTRIC-POWERED

HUSQVARNA K4000

230/120/110 V, 2700/1800/2200 W, 8.5 kg (incl. Vac attachment 1 kg), blade size 350 mm, max. cutting depth 125 mm.



ELECTRIC-POWERED

HUSQVARNA K4000 CUT-N-BREAK

230/120/110 V, 2700/1800/2200 W, 8.9 kg, blade size 230 mm, cutting depth 400 mm.

DIAMOND TOOLS FOR POWER CUTTERS



- G HUSQVARNA ELITE-CUT**
ELITE-level blades with Exo-Grit segments for a smooth, efficient cut – even in reinforced concrete. Diameters 300–400 mm in several versions optimised for different materials.



- S HUSQVARNA VARI-CUT**
VARI-level blades tailored for demanding professionals working on a variety of quick jobs. The new increased segment height provides higher speed and extended blade life. Diameters 300–400 mm in several versions optimised for different materials.



- B HUSQVARNA TACTI-CUT S 35 S BAT**
Providing a good balance between performance and price in all cutting operations.



- B HUSQVARNA TACTI-CUT S 35 S PACE™**
Providing a good balance between performance and price in all cutting operations.



- G HUSQVARNA CUT-N-BREAK BLADE**
For the K 760/K 4000 Cut-n-Break, ELITE-level blades with a segment shape that produces excellent cutting characteristics and performance. Available in three hardness levels.



- G HUSQVARNA ELITE-RING**
ELITE-level ring saw blades designed for optimal cutting speed, even in the hardest reinforced concrete. Three hardness levels. Available in Pre-Cut version with 6.0 mm-wide segments. Diameters 370 and 425 mm.



- B HUSQVARNA TACTI-CUT**
TACTI-level blades optimised for less intensive professional cutting in most materials. Diameters 300–400 mm in several versions optimised for different materials.



- G HUSQVARNA ELITE-CUT S 35 S BAT**
Providing maximum cutting speed and wear resistance in all heavy cutting jobs.



- S HUSQVARNA RESCUE BLADES**
Blades with brazed diamond technology for all-round free cutting in materials such as concrete, rubber, brick, metal and steel, etc. Suitable for rescue applications. Diameters 300–400 mm.



- G HUSQVARNA ABRASIVE DISCS**
S Top-grade abrasive discs that can cut practically any material, such as stone, steel and railway rail. Diameters 300–400 mm.



- S HUSQVARNA VARI-RING**
VARI-level ring saw blades available in three hardness levels. Diameters 370 mm and 425 mm.



- G HUSQVARNA ELITE-GUIDE BAR 450MM/18"**
Guide bars developed to be the optimal choice of cutting equipment for any Husqvarna concrete chainsaw. Fits on both new and older models of Husqvarna concrete chainsaws.



- G HUSQVARNA ELITE-CHAIN 450MM/18"**
A range of professional, premium and quality chains for sawing in reinforced concrete and other construction materials.



- S HUSQVARNA VARI-CHAIN 450MM/18"**
Ideal for demanding professionals, this is a chain that delivers high cutting speed in various all-round construction applications.

CUTTING TROLLEYS



- HUSQVARNA KV 7**
Cutting trolley designed for K 760 and K 770. Water tank 13.3l.



- HUSQVARNA KV 9/12**
Cutting trolley designed for K 970 and K 1270. Water tank 13.3l.

ACCESSORIES FOR POWER CUTTERS



- BATTERY-POWERED HUSQVARNA WT 15i**
Compact and easy-to-use water tank with electric pump. Has a capacity of 15 litres and allows for continual cutting for 45 minutes. Battery-powered. 36V BLi system.



- HUSQVARNA WT 10 MP**
Pressurised water tank, superb when there's no water supply. Pump a few times for the required work pressure. Hose included for connecting to the machine's wet cutting kit. Holds 10 litres.



- HUSQVARNA PIPE CLAMP KIT**
For use with Husqvarna K 970 Ring and Chain and K 7000 Ring and Chain. A convenient accessory for producing straight, precise cuts in concrete and iron pipes.



- HUSQVARNA RA 10**
Cutting attachment for the K 1260 Rail. 5.3 kg.



- HUSQVARNA K 3000/K 4000 VAC ATTACHMENT**
Ideal dust collection enables you to cut without water. Fits K 3000 Wet/Vac and K 4000.

EQUIPPED FOR THE JOB

SmartGuard™ is a line of innovative protective equipment, with features that help you do your job efficiently and in control of your operational safety – without compromising on your comfort or mobility.



- HUSQVARNA SMARTGUARD™ HELMET PE 10 H**
A robust and lightweight helmet with a special chin guard aiming to increase protection of the operator's face. Complete with visor, hearing protection and room for an anti-dust mask and personal eye protection.



- HUSQVARNA SMARTGUARD™ JACKET PE 10 J**
The SmartGuard™ jacket is made with reinforced material aiming to increase protection of the operator's neck and chest. The jacket offers comfortable movement, high visibility according to EN20471 class 2. Removable sleeves, smart pockets and ventilation. Sizes S–XXL.

- HUSQVARNA SMARTGUARD™ BLADE COVER**
Reduces the risk of severe injury from kickbacks and promotes correct technique by guiding the user to the cutting zone.



CUP WHEELS FOR HAND GRINDERS



G HUSQVARNA ELITE-GRIND T-REX SUPER/O

Hard, fast-grinding cup wheels for aggressive removal of floor coatings. For use in the initial stage. Available in two variants for different surfaces. The shape allows better edge reach and pressure distribution.



G HUSQVARNA ELITE-GRIND STAR M/H

A complete series of fast-grinding cup wheels. Offers a high removal rate and long life.



S HUSQVARNA VARI-GRIND ARROW

Medium-hard cup wheels with arrow-shaped segments specially designed for optimal coating removal in a shorter time.



S HUSQVARNA VARI-GRIND

Providing efficient grinding in all materials. Diameters 110–180 mm in four variants for different applications.



B HUSQVARNA TACTI-GRIND

A series of entry-level cup wheels developed for less intensive use. Offers a good performance-cost balance.

NEW



G HUSQVARNA ELITE-GRIND TRANSITION

Cup wheel with ceramic bond and turbo segments, designed to reduce scratches before the first polishing stage.

RESIN TOOLS FOR HAND GRINDERS



S HUSQVARNA VARI-POLISH VP EDGE W/D

A series of resin-bonded tools for handheld polishing concrete, terrazzo and marble. Velcro attachment.



G HUSQVARNA ELITE-POLISH EP EDGE D

Designed to reduce the active surface, increasing the pressure on the floor with higher performance to achieve maximum gloss in fewer steps. Universal Velcro attachment.



B HUSQVARNA TACTI-POLISH TF EDGE D

Entry level tool for handheld polishing in a wide variety of grit sizes, designed with flexible backing to easily follow surface irregularities. The VELCRO® Brand attachment ensures universal compatibility.

D = Dry

W = Wet

DIAMOND BLADES FOR HAND GRINDERS



G HUSQVARNA ELITE-CUT

Blades providing maximum cutting speed and life. Diameters 115–230 mm in six variants for different applications.



S HUSQVARNA VARI-CUT

Blades with a high cutting speed and wear resistance in all materials. Diameters 115–230 mm in nine variants for different applications.



B HUSQVARNA TACTI-CUT

Optimised for less intensive professional cutting in most materials. Diameters 115–230 mm in six variants for different applications.

ANGLE/HAND GRINDERS

NEW



BATTERY-POWERED HUSQVARNA HG 125 B

1500 W equivalent, grinding width 125 mm, disc speed 11,000 rpm, 2.2 kg (excl. battery). Compatible with Bosch Professional 18 V tools and chargers.



ELECTRIC-POWERED

HUSQVARNA BHG 125 G5

2200 W, speed 4500–9500 rpm, grinding width 125 mm, 5.8 kg.



ELECTRIC-POWERED

HUSQVARNA BGV 180 AVO

2600 W, speed 6600 rpm, grinding width 180 mm, 5.4 kg.



ELECTRIC-POWERED

HUSQVARNA BGV 125 AV

1300 W, speed 11,000 rpm, grinding width 125 mm, 3.2 kg.



ELECTRIC-POWERED

HUSQVARNA BHG 180 G180

2200 W, speed 3500–5800 rpm, grinding width 180 mm, 5 kg.



ELECTRIC-POWERED

HUSQVARNA BHG 125 G125

2200 W, speed 4300–7200 rpm, grinding width 125 mm, 4.7 kg.



ELECTRIC-POWERED

HUSQVARNA BHG 180 G7

2200 W, speed 3200–6500 rpm, grinding width 180 mm, 5.7 kg.

TILE AND MASONRY SAWS



ELECTRIC-POWERED

HUSQVARNA TS 400 F

1500/2200 W, max Ø 400 mm, max cutting depth 125/230 mm, 96 kg.



ELECTRIC-POWERED

HUSQVARNA TS 350 E

1500/2200 W, max Ø 350 mm, max cutting depth 100 mm, 92 kg.



ELECTRIC-POWERED

HUSQVARNA TS 300 E

2200 W, max Ø 300 (350) mm, max cutting depth 80 (100) mm, 82 kg.



ELECTRIC-POWERED

HUSQVARNA TS 73 R

1000 W, max Ø 230 mm, max cutting depth 50/100 mm, 47 kg.



ELECTRIC-POWERED

HUSQVARNA TS 66 R

800 W, max Ø 200 mm, max cutting depth 40 mm, 41 kg.



ELECTRIC-POWERED

HUSQVARNA TS 60

1800 W, max Ø 254 mm, max cutting depth 78/45 mm, 36 kg.



ELECTRIC-POWERED

HUSQVARNA TS 100 R

2200 W, max Ø 350 mm, max cutting depth 105 mm, 106 kg.

DIAMOND BLADES



G HUSQVARNA ELITE-CUT

ELITE-level blades for fast, smooth cutting in most construction materials, at the lowest cutting cost per square metre. Diameters 300–1000 mm, in standard or silent variants for different models and applications.



G HUSQVARNA ELITE-CUT G52

Specific for tiles. Available in diameters 180–350 mm.

WALL SAWS

NEW



ELECTRIC-POWERED HUSQVARNA WS 8

High frequency, wireless remote control, diamond blade 500–900 mm, 19 kg, cutting depth 395 mm.

ELECTRIC-POWERED

HUSQVARNA WS 482 HF

High frequency, wireless remote control, diamond blade 600–1600 mm, 28 kg, cutting depth 730 mm.

ELECTRIC-POWERED

HUSQVARNA WS 440 HF

High frequency, wireless remote control, diamond blade 600–1200 mm, 25 kg, cutting depth 530 mm.

ELECTRIC-POWERED

HUSQVARNA WSC 40

Attachment that converts your Husqvarna WS 482 HF and WS 440 HF from blade to chain sawing. Max cutting depth, 400 mm, 19 kg.

DIAMOND TOOLS FOR WALL SAWS



G HUSQVARNA W 1600 SERIES

ELITE-level blades for wall saws, with controlled distribution of the diamonds, optimising it for wall saw cutting, securing consistent performance from start to finish and throughout the blade's life, resulting in a smoother experience for the operator. Diameters 500–2000 mm.



S HUSQVARNA W 1100 SERIES

VARI-level blade for Husqvarna hydraulic and electric wall saws with an ideal design. Fits other machines as well. Diameters 600–1200 mm in three variants for different applications.



G HUSQVARNA DIAMOND CHAINS AND GUIDE BAR

ELITE-level diamond chains optimised for use with WSC 40, developed for sawing in reinforced concrete and other construction materials with different hardnesses.

WIRE SAWS



HYDRAULIC-POWERED HUSQVARNA CS 2512

Wire speed 20 or 25 m/s, magazine capacity 12 m (ready to use 15 m), 150 kg.



ELECTRIC-POWERED HUSQVARNA CS 10

Wire speed 24 m/s, magazine capacity 10 m, 138/135 kg.

DIAMOND WIRES

HUSQVARNA ELITE-WIRE, VACUUM-BRAZED RANGE

Our wires for demanding applications such as cutting pure steel or alloys and highly reinforced concrete. Delivers excellent performance/life balance.



HUSQVARNA ELITE-WIRE, HYBRID RANGE

Our wires for wet cutting in medium to highly reinforced concrete. Delivers high productivity/speed while maintaining an optimal price/performance ratio.



HUSQVARNA VARI-WIRE, SINTERED RANGE

Our wires for cutting medium-reinforced concrete. Delivers good performance/life balance in all-round construction, demolition and refurbishing applications.



POWER PACKS



ELECTRIC-POWERED HUSQVARNA PP 518

20, 30, 40 l/min, 140 bar, 10.4 kW, 145 kg.



ELECTRIC-POWERED HUSQVARNA PP 455 E

65 l/min, 230 bar, 25 kW, 139 kg.



ELECTRIC-POWERED HUSQVARNA PP 325 E

40 l/min, 140 bar, 9.3 kW, 95 kg.

NEW



ELECTRIC-POWERED HUSQVARNA PP 8

3-phase/1-phase 6.5 kW, 18 kg. With radio receiver for operation of WS8.



ELECTRIC-POWERED HUSQVARNA PP 492

20 kW, 25 kg.



ELECTRIC-POWERED HUSQVARNA PP 70

3-phase/1-phase 6.5 kW, 18 kg.

FLOOR SAWS



ELECTROHYDRAULIC-POWERED

HUSQVARNA FS 7000 DL

Diamond blade max 1500 mm, 1338 kg, cutting depth 625 mm, 55.4 kW*.



ELECTROHYDRAULIC-POWERED

HUSQVARNA FS 7000 D

Diamond blade max 1000 mm, 1032 kg, cutting depth 411 mm, 55.4 kW*.



ELECTROHYDRAULIC-POWERED

HUSQVARNA FS 5000 D

Diamond blade max 900 mm, 771 kg, cutting depth 374 mm, 35.5 kW*.



ELECTROHYDRAULIC-POWERED

HUSQVARNA FS 4800 D

Diamond blade max 900 mm, 680–695 kg, cutting depth 381 mm, 35 kW*.



ELECTROHYDRAULIC-POWERED

HUSQVARNA FS 3500 EFI G

Diamond blade max 750 mm, 419 kg, cutting depth 311 mm, 27.5 kW*.



ELECTRIC-POWERED

HUSQVARNA FS 600 E / FS 500 E

Diamond blade max 600/500 mm, cutting depth 240/192 mm, 178/145 kg, 7.5 kW*.



PETROL- / ELECTRIC-POWERED

HUSQVARNA FS 500 SERIES

Diamond blade max 600/500 mm, cutting depth 241/179 mm, 231/197, FS 524, petrol, 15.5 kW*. FS 513, petrol, 8.7 kW*.



DIESEL- / PETROL-POWERED

HUSQVARNA FS 400 SERIES

Diamond blade max 500 mm, cutting depth 189 mm, 163 kg, FS 413, petrol, 8.7 kW*. FS 410D, diesel, 6.6 kW*.



PETROL-POWERED

HUSQVARNA FS 400 LV

Diamond blade max 450/500 mm, cutting depth 162/189 mm, 99/120 kg, 8.7 kW*.



PETROL-POWERED

HUSQVARNA FS 300 SERIES

Diamond blade max 350 mm, cutting depth 122/125 mm, 64/54 kg, FS 309, petrol, 6.6 kW*. FS 305, petrol, 3.6 kW*.

DIAMOND BLADES FOR FLOOR SAWS

HIGH- AND MID-POWERED FLOOR SAWS



G HUSQVARNA F1500 SERIES

ELITE-level blades for floor saws, delivering superior performance. Available in variants optimised for efficient cutting in cured concrete, hard concrete and asphalt. Diameters 500–1500 mm.



G HUSQVARNA F600 SERIES

ELITE-level blades for machines with motors of 25–50 kW. Diameters 300–1200 mm in four variants for different applications.



G HUSQVARNA L600 SERIES

ELITE-level blades for slot cutting and traffic loops with sandwich design. Available in two variants with 6.8 or 10-mm segment widths. Diameters 350–450 mm.

LOW-POWERED FLOOR SAWS




G HUSQVARNA ELITE-CUT

ELITE-level blades with Exo-Grit segments for smooth, efficient cut – even in heavily reinforced concrete. Diameters 300–600 mm in several variants optimised for different materials.




S HUSQVARNA VARI-CUT

VARI-level blades with a high cutting speed and wear resistance. Diameters 300–500 mm in three variants optimised for different materials.



B HUSQVARNA TACTI-CUT

TACTI-level blades optimised for less intensive professional cutting in most materials. Diameters 300–400 mm in three variants optimised for different materials.



WHEN YOU'RE UP TO BUILD A SOLID STRUCTURE, WE'RE A SOLID PARTNER

To build a solid concrete structure you always need to start by ensuring a solid ground layer. That's why we offer one of the industry's most comprehensive range of ground compaction equipment. And with our range of well-proven concrete placement equipment, you'll manage all stages and any size of concrete job. Go to husqvarnaconstruction.com for more information.



COMPACTION EQUIPMENT

NEW



DIESEL-POWERED
HUSQVARNA LT 8005
3kW, 92–93kg.



PETROL-POWERED
HUSQVARNA LT 6005
2.7kW, 69–70kg.



PETROL-POWERED
HUSQVARNA LT 5005
2.7kW, 61–62kg.

NEW



FORWARD PLATE COMPACTOR
LF 60i LAT
1.2kW, 350mm, 69kg. Ideal for hardscaping work. Includes water tank, transport wheels and low-vibration handle. Optional block paving kit available.



FORWARD PLATE COMPACTOR
HUSQVARNA LFe 60 LAT
1.8kW, 350mm, 88kg. Runs on Honda eGX battery platform, specifically developed for compaction applications.



PETROL-POWERED
HUSQVARNA LX 90
3.6kW, 450mm, 96kg.



PETROL-POWERED
HUSQVARNA LF 50 L
2.3kW, 320mm, 53kg.



PETROL-POWERED
HUSQVARNA LF 80 L
3.6kW, 420mm, 84kg.



PETROL-POWERED
HUSQVARNA LFV 60
2.4kW, 350mm, 64kg.



PETROL-POWERED
HUSQVARNA LFV 80
3.6kW, 420mm, 80kg.



PETROL-POWERED
HUSQVARNA LFV 100
3.6kW, 500mm, 91/101kg (petrol/diesel).



PETROL-POWERED
HUSQVARNA LF 60 LAT
2.3kW, 350mm, 67kg.



PETROL-POWERED
HUSQVARNA LF 75 LAT
3.6kW, 420–500mm, 95–97kg.



PETROL-POWERED
HUSQVARNA LF 80 LAT
3.6kW, 420mm, 95kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LF 100 LAT
2.5–3.6kW, 500mm, 109–118kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LF 130 LAT
2.5–3.6kW, 500mm, 135–142kg.



DIESEL-POWERED
HUSQVARNA LH 700
11kW, 780kg.



DIESEL-POWERED
HUSQVARNA LH 804
11kW, 820kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LG 164
3.1–3.6kW, 148–185kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LG 204
3.1–4.1kW, 211–251kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LG 300
4.7–5.3kW, 265–307kg.



DIESEL-/PETROL-POWERED
HUSQVARNA LG 400
6.2–8.3kW, 398–436kg.



DIESEL-POWERED
HUSQVARNA LG 504
9.2kW, 470–513kg.



DIESEL-POWERED
HUSQVARNA LP 9505
18kW, drum width 850mm, 1680kg.



DIESEL-POWERED
HUSQVARNA LP 7505
7.9kW, drum width 750mm, 981–1001kg.



DIESEL-POWERED
HUSQVARNA LP 6505
7.2kW, drum width 650mm, 745–765kg.

HIGH FREQUENCY ELECTRIC VIBRATORS



ELECTRIC-POWERED
HUSQVARNA SMART VIBRATORS
1-phase, \varnothing 40–65 mm,
hose length 5, 8, 10 m, 13.1–18.5 kg.



ELECTRIC-POWERED
HUSQVARNA SMART-E VIBRATORS
1-phase, \varnothing 40–56 mm,
hose length 0.5 m, 12–14.8 kg.



ELECTRIC-POWERED
HUSQVARNA AX VIBRATORS
42 V–3–200 Hz, \varnothing 36–65 mm, hose length 5, 8,
10 m, 12–18 kg.

ELECTRIC-POWERED
HUSQVARNA VIBRASTAR
42 V–3–200 Hz, \varnothing 40–60 mm, hose length 5 m,
8.4–15 kg.

POWER UNITS FOR AX/VIBRASTAR



ELECTRIC-POWERED
HUSQVARNA CF 67T
Output 42 V–3–200 Hz, 4.7 kVA,
67 A, 70 kg, 4 outlets.



ELECTRIC-POWERED
HUSQVARNA CF 25
Output 42 V–3–200 Hz, 1.8 kVA, 25 A, 31 kg,
2 outlets.



ELECTRIC-POWERED
HUSQVARNA CF 11
Output 42 V–3–200 Hz, 0.8 kVA, 11 A, 18 kg,
1 outlet.

MODULAR FLEX-SHAFT VIBRATORS



ELECTRIC-POWERED
HUSQVARNA AME 1600
1-phase, 1.6 kW, 6.1 kg.



ELECTRIC-POWERED
HUSQVARNA AME 600
1-phase, 0.6 kW, 1.9 kg.



HUSQVARNA SUPERFLEX SERIES
Flexible shafts 1/2/3/4 m, 2.4–7.3 kg.



HUSQVARNA HA SERIES
 \varnothing 25/35 mm, hose lengths: 1/2/3 m,
2.8–7.6 kg.



HUSQVARNA AT SERIES
Vibrator heads, \varnothing 29–59 mm, 1.3–3.9 kg.



ELECTRIC-/PNEUMATIC-POWERED
HUSQVARNA VIBRATORS
7 versions, speed 3000–6000 rpm,
max. centrifugal force 1400–16000 N.

EXTERNAL VIBRATORS

MECHANICAL VIBRATORS



PETROL-POWERED
HUSQVARNA AMG 3200
Drive unit for AA and AZ vibrators, 2.8 kW, 15 kg.



HUSQVARNA AA SERIES
Hose length 6/4.8 m, 4 diameters: 39–75 mm.



HUSQVARNA AZ SERIES
Hose length 6/4.8 m, 4 diameters: 25–55 mm.



PNEUMATIC-POWERED
HUSQVARNA AY SERIES
7 diameters, 26–155 mm, hose length 2 or 4 m,
4–28 kg.



BATTERY-POWERED
HUSQVARNA BV 30i
Output power 0.8 kW, weight 11.5 kg, BLi 36 V
battery system.



PETROL-POWERED
HUSQVARNA BV 30
1 kW, centrifugal clutch, 14 kg.



HUSQVARNA BV 30 SCREED BLADE
1.8/2.4/3.0/3.6/4.2 m.



HUSQVARNA BV 20 H
2.0 m, 7.5 kg.



PETROL-POWERED
HUSQVARNA BV 20 G
2 m, 0.7 kW, 16.6 kg.



HUSQVARNA BE 20
0.45 kW, 37 kg.



HUSQVARNA BD 32/42/52/62
3.2, 4.2, 5.2, 6.2 m, 32–57 kg.

PNEUMATIC VIBRATORS

MODULAR SCREEDS



ELECTRIC-POWERED
HUSQVARNA BT 90 E
3 kW, 20 m, 96 kg.



PETROL-POWERED
HUSQVARNA BT 90 G
5 kW, 20 m, 93 kg.



HUSQVARNA BT 90 G/E SCREED SECTION
0,5/0,75/1/2/3 m.



HUSQVARNA BT 90 CROWN INVERT BRACKET
267 mm, maximum angle 15°.

RIDE-ON TROWELS AND POWER TROWELS



PETROL-POWERED
HUSQVARNA CRT 48 PS
Ideal for finishing surfaces 1000–2300 m². The power steering enables accurate manoeuvring and virtually fatigue-free operation with two control modes to accommodate operator preference in varying site conditions. 42.5 kW, 2×1220 mm, 660 kg.



PETROL-POWERED
HUSQVARNA CRT 48
Ideal for finishing surfaces 1000–1900 m². Featuring a superior mechanical steering system and balanced power-to-weight ratio. 27.6 kW, 2×1220 mm, 579 kg.



PETROL-POWERED
HUSQVARNA CRT 36
Ideal for finishing surfaces 250–1000 m². Featuring a superior mechanical steering system and balanced power-to-weight ratio. 16.5 kW, 2×915 mm, 451 kg.



PETROL-POWERED
HUSQVARNA CT 48
5.9–8.7 kW, 1180 mm, 105–125 kg.



PETROL-POWERED
HUSQVARNA CT 36
3.6–5.9 kW, 875 mm, 85–94 kg.



PETROL-POWERED
HUSQVARNA BG 475
6.3 kW, 1140 mm, 105 kg.



PETROL-POWERED
HUSQVARNA BG 375
3.6–6.3 kW, 900 mm, 88–102 kg.



PETROL-POWERED
HUSQVARNA BG 245
2.5 kW, 600 mm, 58 kg.



ELECTRIC-POWERED
HUSQVARNA BG COMBI
1.8–2.4 kW, 1020–850 mm, 88–86 kg.




ELECTRIC-POWERED
HUSQVARNA BG 245 E
1.5 kW, 600 mm, 60 kg.

TOOLS RIDE-ON TROWELS AND POWER TROWELS



HUSQVARNA HIPERTROWEL™ FLOOR POLISHING SYSTEM
Polish large concrete floors fast with a ride-on power trowel and Hiperflex TRW tool pads mounted on flexible Hipertrowel™ gyro drivers.



HUSQVARNA PROLINE



HUSQVARNA CLASSIC LINE



EARLY ENTRY SAWS



PETROL-POWERED
HUSQVARNA SOFF-CUT 4000
 Diamond blade max 350 mm, cutting depth max 70 mm,
 191 kg, 14.9kW*.



PETROL-POWERED
HUSQVARNA SOFF-CUT 2000
 Diamond blade max 250 mm, cutting depth max 38 mm,
 144 kg, 6.5kW*.

NEW ENGINE



PETROL-POWERED
HUSQVARNA SOFF-CUT 150
 Diamond blade max 150 mm, cutting depth max 30 mm,
 40 kg, 3.5kW*.

DIAMOND BLADES FOR EARLY ENTRY SAWS



HUSQVARNA SOFF-CUT BLADES
 Patented ELITE-level blades, supplied with skid plate. They are developed and tested for aggregate conditions. Soff-Cut blades are of top quality and designed specifically for the Soff-Cut system. Diameters 150–350 mm in three different series.

* As rated by the engine manufacturer.

THE COMPLETE PARTNER IN SURFACE PREPARATION

Open your eyes to the possibilities with the most comprehensive range of solutions for surface preparation in the industry. By combining our extensive know-how with a wider range of machines, we can meet all your surface preparation needs – from shot and steel blasting, to scraping, scarifying, grinding and much more.



FLOOR SCRAPERS AND TOOLS



BATTERY-POWERED
HUSQVARNA BMS 220ADB
Ride-on, 4 kW battery powered, 48V,
1142 kg.



ELECTRIC-POWERED
HUSQVARNA BMS 150
Ride-on, 2.2 kW, 230V/16A,
480 kg.



ELECTRIC-POWERED
HUSQVARNA BS 110
1.5 kW, 230V/16A, 170 kg.



ELECTRIC-POWERED
HUSQVARNA BS 75
1.5 kW, 230V/16A, 128 kg.



HUSQVARNA SCRAPER TOOLS
Flat and self-scoring blades and blade
holders. Husqvarna offers several
optional blades for each different floor
scraper and application.

FLOOR SCARIFIERS AND TOOLS



ELECTRIC-POWERED
HUSQVARNA BMP 4000RC
Remote controlled, 30 kW, 400V/63A, 400 mm working width, 1550 kg.



ELECTRIC-POWERED
HUSQVARNA BMP 335
12 kW, 400V/32A, 335 mm working width, 393 kg.



PETROL-POWERED
HUSQVARNA BMP 265 PETROL
6 kW, Petrol, 265 mm working width, 190 kg.



ELECTRIC-POWERED
HUSQVARNA BMP 265
5.5 kW, 400V/16A, 265 mm working width, 175 kg.



PETROL-POWERED
HUSQVARNA BMP 215 PETROL
4 kW, Petrol, 215 mm working width, 59 kg.



ELECTRIC-POWERED
HUSQVARNA BMP 215
1.8 kW, 230V/16A, 215 mm working width, 63 kg.



PETROL-POWERED
HUSQVARNA CG 200
3.6 kW, Petrol, working width 200 mm, 54 kg.



ELECTRIC-POWERED
HUSQVARNA CG 200
2.2 kW, 220-240 V, grinding width 200 mm, 58 kg.



HUSQVARNA SCARIFYING TOOLS
An ELITE-level range of scarifying drums with different steel and
carbide wheels that cover applications from coating removal
to grooving.

FLOOR SHAVERS AND TOOLS



ELECTRIC-POWERED
HUSQVARNA BMP 4000RC
Remote controlled, 30 kW, 400V/63A, 380 mm
working width, 1550 kg.



ELECTRIC-POWERED
HUSQVARNA BMC 335RC
Remote controlled, 16 kW, 400V/63A,
335 mm working width, 432 kg.



ELECTRIC-POWERED
HUSQVARNA BMC 335
16 kW, 400V/32-63A, 335 mm working width,
430 kg.



HUSQVARNA SHAVING TOOLS
We offer different shaving blades for each
individual machine and application.



HUSQVARNA SHOT BLASTERS AND STEEL BLASTERS

We supply a large range of shot blasting equipment. All our shot blasting machines are characterised by their manoeuvrability, precision and versatility. With all our shot blasters you are able to work in a close to dust-free environment when they are connected to an appropriate dust extractor.

HUSQVARNA SHOT BLASTERS



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 2-48DS

2×22 kW, 400 V, 125 A, working speed
0,5–33 m/min, working width 1220 mm, 1350 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 2-20DT

2×11 kW, 400 V, 63 A, working speed
0,5–33 m/min, working width 550 mm, 575 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-15DS

15 kW, 400 V, 63 A, working speed
0,5–25 m/min, working width 380 mm, 450 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-10DS

11 kW, 400 V, 32/63 A, working speed
0,5–25 m/min, working width 254 mm, 395 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-10DPS75

7,5 kW, 400 V, 16 A, working speed
0,5–30 m/min, working width 254 mm, 211 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-8DPS55

5,5 kW, 400 V, 16 A, working speed
0,5–23 m/min, working width 203 mm, 154 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-8DPF40

4 kW, 400 V, 16 A, working speed
0,5–23 m/min, working width 203 mm, 122 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC 1-8DPS30

3 kW, 230–400 V, 16 A, working speed
0,5–23 m/min, working width 203 mm, 125 kg.

HORIZONTAL STEEL BLASTERS



ELECTRIC-POWERED

HUSQVARNA BLASTRAC EBE 500

(50/60 Hz) 22 kW, 400 V, 63 A, working speed 1–15 m/min, working width 500 mm, 742 kg.



HYDRAULIC-POWERED

HUSQVARNA BLASTRAC EBE 500S

(50/60 Hz) 22 kW, 400 V, 63 A, working speed 1–30 m/min, working width 500 mm, 752 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC EBE 350

11 kW, 400 V, 32 A, working speed 1–15 m/min, working width 350 mm, 430 kg.



HYDRAULIC-POWERED

HUSQVARNA BLASTRAC EBE 350S

11 kW, 400 V, 32 A, working speed 1–30 m/min, working width 350 mm, 415 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC EBE 350EX

11 kW, 400 V, 32 A, working speed 1–15 m/min, working width 350 mm, 450 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC EBE 900V

2×22 kW, 400 V, 125 A, working speed 0.5–10 m/min, working width 890 mm, 880 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC EBE 200V

7.5 kW, 400 V, 32 A, working speed 0.2–20 m/min, working width 217 mm, 177 kg.

DUST COLLECTORS



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 900

17 kW, 400 V, 32 A, 860 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 2-48

18 kW, 400 V, 32 A, 1107 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 975

7.5 kW, 400 V, 63 A, 510 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 200

13 kW, 400 V, 30 A, 360 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 655

6.6 kW, 400 V, 63 A, 481 kg.



ELECTRIC-POWERED

HUSQVARNA BLASTRAC DC 350EX

5.5 kW, 400 V, 63 A, 665 kg.

BLASTRAC MAGNETIC BROOM



HUSQVARNA MAGNETIC BROOM R900



HUSQVARNA MAGNETIC BROOM R600



HUSQVARNA MAGNETIC SWEEPER

ABRASIVES



HUSQVARNA ABRASIVES

S330, S390, S460, S550, S660

PLANETARY GRINDERS



ELECTRIC-POWERED
HUSQVARNA BMG 2200
63 kW, 400 V, 125 A, grinding width 2200 mm,
grinding disc 3x3, 3035 kg.



ELECTRIC-POWERED
HUSQVARNA HTC 950 RX
15 kW, 380–415, 440–480 V, 3-phase,
grinding width 920 mm, grinding disc
4 × 270 mm, 600 kg.



ELECTRIC-POWERED
HUSQVARNA PG 830 RC
16.5 kW, 380–415 V, 3-phase, grinding width
800 mm, grinding disc 3 × 270 mm, 598 kg.



ELECTRIC-POWERED
HUSQVARNA PG 830
16.5 kW, 380–415 V, 3-phase, grinding width
800 mm, grinding disc 3 × 270 mm, 556 kg.



ELECTRIC-POWERED
HUSQVARNA HTC 830 S
11 kW, 380–415 V, 3-phase, grinding width
800 mm, grinding disc 3 × 270 mm, 497 kg.



ELECTRIC-POWERED
HUSQVARNA HTC X8 / HTC RX8
12–15 kW, 380–415 V, 3-phase, grinding width
800 mm, grinding disc 3 × 270/4 × 270 mm,
499/574 kg.



ELECTRIC-POWERED
HUSQVARNA BMG 780 / BMG 780RC
15 kW, 400 V, 32 A–63 A, 3-phase, grinding
width 780 mm, weight 487/639 kg.



ELECTRIC-POWERED
HUSQVARNA PG 690 RC
12.5 kW, 380–415 V, 3-phase, grinding width
640 mm, grinding disc 3 × 270 mm, 598 kg.



ELECTRIC-POWERED
HUSQVARNA PG 690
12.5 kW, 380–415 V, 3-phase, grinding width
640 mm, grinding disc 3 × 270 mm, 502 kg.



ELECTRIC-POWERED
HUSQVARNA HTC X6 / HTC RX6
7.5 kW, 380–415 V, 3-phase, grinding width
600 mm, grinding disc 3 × 230/4 × 230 mm,
384/441 kg.



ELECTRIC-POWERED
HUSQVARNA BMG 555
7.5 kW, 400 V, 16 A, grinding width 555 mm,
298 kg.



ELECTRIC-POWERED
HUSQVARNA HTC 5
4.0–2.2 kW, 400–220 V, 3-phase/1-phase,
grinding width 515 mm, grinding disc
3 × 230 mm, 122/179 kg.



ELECTRIC-POWERED
HUSQVARNA PG 540
4.0–2.2 kW, 400–220 V, 3-phase/1-phase,
grinding width 515 mm, grinding disc
3 × 230 mm, 178/169 kg.



ELECTRIC-POWERED
HUSQVARNA PG 510
4.0–2.2 kW, 400–220 V, 3-phase/1-phase,
grinding width 515 mm, grinding disc
3 × 230 mm, 133/120 kg.



ELECTRIC-POWERED
HUSQVARNA PG 450
2.2 kW, 230 V, 1-phase, grinding width 450 mm,
grinding disc 3 × 180 mm, 109 kg.



ELECTRIC-POWERED
HUSQVARNA BMG 444SC
2.2 kW, 230 V 16 A, grinding width 444 mm,
132/135 kg. Fixed speed/speed control.

SINGLE DISC GRINDERS



ELECTRIC-POWERED
HUSQVARNA PG 400
4 kW, 400 V, 3-phase, grinding width
400 mm, 115 kg.



PETROL-POWERED
HUSQVARNA PG 400 PETROL
Grinding width 400 mm, 140 kg.



ELECTRIC-POWERED
HUSQVARNA PG 280
3–2.2 kW, 400–220 V,
3-phase/1-phase, grinding width
280 mm, 70 kg.



ELECTRIC-POWERED
HUSQVARNA HTC 270 EG
2.2 kW, 230 V, 1-phase, grinding
width 270 mm, 103 kg.



ELECTRIC-POWERED
HUSQVARNA BG 250
5.5 kW, 400 V, 3-phase, grinding
width 250 mm, 146 kg.

METAL TOOLS FOR REMOVAL AND GRINDING



- G** **HUSQVARNA EZ T-REX®**
S EZchange™ tool system with PCD segments for aggressive removal of various types of coatings, resulting in a clean surface with efficiency and precision.



- G** **HUSQVARNA RAVAGER**
S Developed for creating a bush-hammered surface or to expose large aggregates.

NEW



- G** **HUSQVARNA ELITE-GRIND EZ-SERIES**
S EZchange™ tool system consisting of six different tool types to efficiently grind and prepare concrete floors of varying hardness. Achieve smooth and exposed surfaces with a consistent scratch pattern.



- G** **HUSQVARNA ELITE-GRIND SGW**
S Metal bonded tool with cross attachment system specifically designed to smoothly wet grind natural stone floors. Part of the EZchange™ tool system.

NEW



- S** **HUSQVARNA VARI-GRIND EZ-SERIES**
S EZchange™ tool system of concrete grinding tools ideal for users looking for the best price-performance ratio. Available in three bonds and three grit sizes.



- G** **HUSQVARNA GRINDING DISCS**
S 250 mm/10" bolt-on grinding discs for high removal applications. Designed for Husqvarna BGS/BG 250.

NEW



- S** **HUSQVARNA VARI-GRIND EZ SL**
S The wood series is a single-layer diamond tool specifically developed for efficient initial grinding of wood. Part of the EZchange™ tool system.

NEW



- B** **HUSQVARNA TACTI-GRIND EZ-SERIES**
S EZchange™ tool system for concrete grinding where cost is the first criteria of selection. Available in one bond with three grit sizes.



- HUSQVARNA TOOL HOLDERS**
S The Husqvarna EZchange™ tool holder range is designed to maximise productivity while minimising downtime. The tool holders are engineered to support the tools and make the tool-change process hassle-free.

SURFACE TEST EQUIPMENT



- HUSQVARNA BOT3000E FRICTION TESTER**
S A portable fully-automatic instrument to test slip resistance of floors. Measures both SCOF and DCOF in both wet and dry conditions.



- HUSQVARNA MAHRSURF PS10 - ROUGHNESS TESTER**
S A mobile surface roughness tester. Measures 31 parameters, for example Ra, Rz, Rmax.



- HUSQVARNA RHOPPOINT IQ - GLOSS AND DOI METER**
S A powerful mobile surface quality tester. Measures Gloss, DOI and HAZE.



- HUSQVARNA MGE-SS GLOSS CHECKER**
S A portable gloss meter specifically developed for stone. Measuring Angle 60°.



- ICRI PROFILE CONCRETE SET**
S A set of 10 different real concrete samples corresponding with CSP 1-10 according to the globally accepted ICRI specifications.



- ICRI PROFILE PLASTIC CHIPSET**
S A chipset with 10 different plastic samples corresponding with CSP 1-10 according to the ICRI specifications.



- HUSQVARNA MOHS TEST KIT SURFACE HARDNESS TESTER**
S A scratch test kit to determine the hardness of concrete or any hard floor in relation to the Mohs scale.



- PENETRATION TEST - KARSTEN PIPE TEST KIT**
S A water penetration test kit used as a rapid testing procedure of water penetration in building materials.

FLOOR TREATMENT PRODUCTS



- FLOOR GROUTING SYSTEM**
S For pore filling of pinholes and micro cracks in concrete surfaces: GM 3000 20I, GM+ 9I.



- FLOOR HARDENING SYSTEM**
S For making concrete more wear resistant and dust-free: CURE (K) 20I, CURE (L) 20I, CURE+ 20I/200I.



- FLOOR PROTECTION SYSTEM**
S For protecting the surface against stains: Premium Guard WB 5I/10I, Premium Guard SB 5I/10I, Topical Guard 20I, Topical Guard Color LG 20I, Topical Guard Color DG 20I.



- FLOOR CLEANING SYSTEM**
S For cleaning and maintenance: Clean & Protect 5I.

RESIN TOOLS FOR POLISHING

NEW



- G** **HUSQVARNA ELITE-POLISH ET D**
S For the efficient removal of scratches and a safer transition when shifting from metal to resin bonded tools. EZchange™ attachment system.




- G** **HUSQVARNA ELITE-POLISH EP D**
S This high-performing concrete polishing tools series performs on all types of concrete. EZchange™ attachment system.



- G** **HUSQVARNA ELITE-POLISH EF W/D**
S Premium resin technology with an optimised flexible design to achieve a high level of polishing and gloss. EZchange™ attachment system.



- G** **HUSQVARNA ELITE-POLISH EB/EM W/D PADS**
S Diamond-impregnated maintenance pads, ideal for cleaning polished concrete floors. Fits both auto scrubbers and grinding machines. Velcro® or EZchange™ attachment system.



- G** **HUSQVARNA ELITE-POLISH EX D**
S Top-of-the-line tools for dry grinding and polishing of natural stone surfaces. EZchange™ attachment system.



- S** **HUSQVARNA VARI-POLISH VT W/D**
S Serves as the ideal starting point when the surface is too rough to begin directly with polishing tools. Available for wet or dry applications. Universal VELCRO® brand attachment.



- S** **HUSQVARNA VARI-POLISH VP W/D**
S Resin bond polishing pads can be chosen for high-end polishing. Grit range from 50 to 3,000. Universal VELCRO® brand attachment.



- S** **HUSQVARNA VARI-POLISH VF D**
S Optimal for polishing concrete and cementitious toppings such as overlays or screed. It's the best troubleshooting product for all kinds of problems.



- S** **HUSQVARNA VARI-POLISH VS D**
S Specially designed for sanding when restoring wooden floors. Universal VELCRO® brand attachment for use on any machine. Use together with Husqvarna Foamflex pads.



- B** **HUSQVARNA TACTI-POLISH TP D**
S Entry-level polishing pucks for stress-free polishing in a wide range of grit sizes. Universal VELCRO® brand attachment.



- B** **HUSQVARNA TACTI-POLISH TT W**
S Polishing pucks optimal for the transition process. Suitable for wet applications. Universal VELCRO® brand attachment.



- G** **HUSQVARNA ELITE-POLISH EO D**
S A high-performance, resin-bonded transitional tool for cementitious overlays. Universal VELCRO® attachment for use on any machine.



- S** **VARI-POLISH VC D**
S Diamond-infused triangular pads, designed for precision edge grinding of corners leaving no untouched areas. Universal VELCRO® brand attachment for use on any machine.

D = Dry
W = Wet